

CH-T240/TPC-5401-7.5/POE/SW

IP thermal camera station



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Type	CH-T240/TPC-5401-7.5/POE/SW
WISKA-Order no.	10110861
Material	Stainless steel
Surface	Powder coated
Colour	RAL 9016
Operational areas	Outdoor
Weight	5,6 kg
Protection class	IP68
Temp. range min	-40 °C
Temp. range max	70 °C
Humidity	100 %
Resolution	400x300
Image Sensor	Uncooled Micro bolometer
Video Standard	Digital
Video Streaming	H.264/MJPEG
Zoom	Yes
Zoom (opt. x digi.)	digital zoom
Frames per Second	25
Lighting Conditions	Thermal image uncooled
Wash&Wipe	No
Min. illumination	0.0 lx
Angle of View (horizontal)	53.7°
Angle of View (vertical)	39,7°
Detection	490m
Pan/Tilt	Hand operated

Your Contact:

WISKA Electric Systems (Shanghai) Co., Ltd · 维司卡电气设备(上海)有限公司

Room 703, Building 4, No. 258 Jinzang Road, Pudong Jinqiao Export Processing Zone, Shanghai, P.R.China 201206

上海市浦东新区金桥出口加工区金藏路258号4号楼703室 201206

☎ +86-21-58440056 · ☎ +86-21-58440027 · 📠 +86-21-58440031 · contact@wiska.cn · www.wiska.cn

Presets P/T	No
Rotation horizontal	360 °
Rotation vertical	+80 ° / -80 °
Vibration (0-100Hz)	2,3 g
Voltage	48 V
Type of Voltage	POE (IEEE 802.3af)
Wattage	13 W
Junction box required	Yes
CCTV add-on	Multistreaming
Tariff number	85255000

Remarks:

IP POE Thermal Image Camera Outdoor,
 CH-T240, IP68
 Uncooled micro bolometer, without heating
 resolution 400x300, H.264/Motion JPEG
 Up to 30fps (export control regulations
 refers)
 Detection range: ~490m
 Object size: 4,0x1,4m
 Lens: 7,5 mm
 Spectral range: 8 ~ 14 µm
 Power supply: PoE (not included)
 Mounting type: WISKA Searchlights, etc.
 //fixed side mounting (left)//

22.07.2026

Your Contact:

WISKA Electric Systems (Shanghai) Co., Ltd · 维司卡电气设备(上海)有限公司
 Room 703, Building 4, No. 258 Jinzang Road, Pudong Jinqiao Export Processing Zone, Shanghai, P.R.China 201206
 上海市浦东新区金桥出口加工区金藏路258号4号楼703室 201206
 ☎ +86-21-58440056 · ☎ +86-21-58440027 · 📠 +86-21-58440031 · contact@wiska.cn · www.wiska.cn