

TECHNICAL DATASHEET

TERMINAL BLOCK TYPE HKT 1010

WISKA Hoppmann GmbH
Kisdorfer Weg 28
24568 Kaltenkirchen
Germany



Product designation:	Terminal Block
Type of terminal:	5-pole screw terminal
WISKA type:	HKT 1010
Nominal cross-section:	16 mm ²
Rated voltage:	400 V
Rated current:	80 A
Ambient temperature:	-30°C +80°C
Screw torque:	2 Nm
Test standard	DIN EN 60998-1 (EN 60998-1 / IEC 60998-1) DIN EN 60998-2-1 (EN 60998-2-1 / IEC 60998-2-1)

Number of conductors per terminal point / pole

Cross-section [mm ²]:	4				6				10				16			
	s	r	f	s	r	f	s	r	f	s	r	f	s	r	f	s
Conductor type ^{A)} :																
Minimal	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Maximum	8	8	5	6	6	4	3	3	2	2	2	2	--	--	--	--

^{A)} s = solid, r = rigid, f = flexible (with wire-end ferrules)

WISKA part No.:	30072367
Spare part No.:	22000408
Material	Terminal base: Copper-zinc alloy (brass), uncoated Terminal housing: Polyamide with GWIT = 850°C Screws: Steel, zinc-plated Terminal holder: Polypropylene, glass-fibre reinforced, GWIT = 750°C
Supplier:	201626 Base type: 112-11862000-00 5-pole type: 112-11862500-00 (WISKA-No. 50085230)
Suitable for:	COMBI 1010, COMBI INDUSTRY 1010, COMBI 1210

